THE AIRDRI GROUP

TECHNICAL SHEET

# PureDRI

## Hand Dryer & Sanitiser Combined

Designed to deliver three points of infection control, fast-dry hand drying and exceptional energy efficiency, the PureDRI station substantially reduces contamination risk whilst creating cleaner, fresher smelling and more sustainable washroom environments.

- **Continuous room sanitising**
- **No-touch infra-red hand drying**
- **In-built sanitising lamp**

**Talk to an expert.** airdri.com

| DRY TIME | NOISE OUTPUT | RATED POWER | RUNNING COST / YR |
|---|---|---|---|
| 20 secs | 76 dBA | 0.2 kW | £65 |

Noise output: Tested at ISVR Consulting, Southampton University Audio Labs UK. Running cost: Based on 200 washes per day, 365 days per year. The 2024 average commercial electricity cost is 20 pence per kilowatt hour.

TECHNICAL DATA

# PureDRI

| In-built | 5 Year | 76 dBA | 0.2 kW |
|---|---|---|---|
| Sanitising lamp | Warranty | Noise output | Rated power |

| | |
|---|---|
| **Dimensions** | 270 × 820 × 100 mm |
| **Weight** | 9.2 kg |
| **Electrical supply** | 110VAC – 240VAC 50/60Hz |
| **Current consumption** | 1.7 A @ 115VAC / 0.9 A @ 230VAC |
| **Power consumption** | 0.2 kW (220W) |
| **Drying speed** | 20 seconds |
| **Control system** | Room sanitising: continuous. Hand drying & sanitising: automatic, infra-red, no-touch |
| **Aperture type** | Concentrated jet |
| **Air velocity** | 50 m/s / 112 mph (100 mm vertically under outlet) |
| **Air outlet temperature** | 30°C at 20°C ambient |
| **Noise level** | 76 dBA at 1 meter (3 ft) from dryer |
| **Cover options** | Brushed stainless steel |
| **Lamp options** | 3mg ozone bulb as standard. 0mg non-ozone bulb available |

COLOUR OPTIONS

Stainless steel / White

**Noise output:** Tested at ISVR Consulting, Southampton University Audio Labs UK

**Running cost:** Based on 200 washes per day, 365 days per year. The 2024 average commercial electricity cost is 20 pence per kilowatt hour